

GROUP HOME (R-4 Occupancy) PLANS CHECKLIST

Development Services Department

90 E. Civic Center Dr. Gilbert, AZ 85296 (480) 503-6700-Ph. (480) 497-4923-Fax www.gilbertaz.gov

Admin Review by_____

A Community of Excellence

Group Home checklist 1/7/15

ALL THREE PLAN SETS SHALL BE SUBMMITED AT THE SAME TIME

In order to provide excellent service to the Town of Gilbert's customers, each submittal must meet the minimum requirements as listed on this form, or your submittal will not be accepted by the Development Services Staff.

Appi	icant	Stair
	Provide FIRE SPRINKLER PLANS with a separate "Permit Application" from contractor (NFPA 13-D Modified with coverage in bathrooms, garages, closets and covered patios/entries)	
П	Provide FIRE ALARM PLANS with a separate "Permit Application" from contractor	
	(Fire Sprinkler System shall be monitored offsite by an approved listed central monitoring station)	
	Provide Dimensioned FLOOR PLAN that show compliance with all of the following requirements	
	FLOOR PLAN FOR HOMES WITH 1 to 10 OCCUPANTS*	
	Show an Emergency escape & rescue opening for each sleeping room that complies with current codes	
	Show Smoke Alarms in each habitable room and hallway installed per current code requirements (Hardwired, interconnected with battery backup)	
	Show Carbon Monoxide monitors installed per current code requirements	
П	Show location of 2A10BC fire extinguisher(s)	
_	(1 per 3000 square feet, with maximum travel distance of 75 feet)	
	Add note that "Portable Heating Equipment is not permitted"	
	Add note that International 4"x4" No Smoking symbol will be posted at all entrances	
$\overline{\Box}$	Post Fire Safety and Evacuation Plan	$\overline{\Box}$
_	(Route from sleeping rooms to exit must <u>not</u> pass through sleeping rooms, bathrooms, laundry rooms, or garage:	s)
	FLOOR PLAN FOR HOMES WITH 1 to 5 OCCUPANTS* Show location of code compliant exit access door (Must not pass through sleeping rooms, kitchens, laundry rooms, or garages)	
	FLOOR PLAN FOR HOMES WITH 6 to 10 OCCUPANTS*	
	Show location of TWO code compliant exit access doors	
	(Maximum travel distance from center point of sleeping rooms to an exit shall not exceed 75 feet) (Must be located a distance apart of not less than one third the maximum diagonal dimension of home)	
	Show location of signs for Exit path and Exit access doors (90 minute emergency backup power source required)	
	Show location of means of Egress lighting from each room to Exit access doors (A light is required outside of each required exit door) (90 minute emergency backup power source required) ** Occupant is a person receiving care	
Th a	*** Exit access doors must be side hinged, be 3 feet in width and 6 feet 8 inches in height (no sliding doors) **** Homes for 6 to 10 Occupants must comply with Section 425.2 of the 2012 IBC (amended) Town of Gilbert is currently enforcing the 2012 IBC, IRC & IFC with the Town, State and Maricopa Association of	